

BABA R6 EVO

Recessed optics downlights

design Roberto Mantovani



A range of recessed fixtures that combines an extremely refined and minimal design with a high visual comfort: the extremely thin edge and recessed optics make for an innovative and effective element. Equipped with Fidelity LED it places emphasis on CRI98 and R9 93. Available in eight finishes, three colour temperatures and three extremely clean and performing optics.

Un gamma di incassi che associa un design estremamente curato e minimale ad un elevato comfort visivo: il bordo estremamente ridotto e l'ottica arretrata ne fanno un elemento innovativo ed efficace. Equipaggiato con LED Fidelity si connota per un CRI98 e R9 93. Disponibile in otto finiture, tre temperature colore e tre ottiche estremamente pulite e performanti.

Une gamme d'encastrables qui associe un design extrêmement soigné et minimaliste à un confort visuel élevé : le bord extrêmement réduit et l'optique en retrait en font un élément innovant et efficace. Équipé avec LED Fidelity il se caractérise par un CRI98 et R9 93. Disponible dans huit finitions, trois températures couleur et trois optiques extrêmement propres et performantes.

Eine Serie von Einbauleuchten, die ein äußerst präzises und minimalistisches Design mit hohem Sehkomfort verbindet: Die extrem reduzierte Kante und die rückwärtige Optik machen sie zu einem innovativen und wirkungsvollen Element. Ausgestattet mit Fidelity-LEDs zeichnet sie sich durch einen CRI98 und R9 93 aus. Erhältlich in acht Ausführungen, drei Farbtemperaturen und drei extrem sauberen und leistungsstarken Optiken.

IP44 made in Italy



Supply current


500mA (V_i 9V)

Power


6W

Series wiring

Dimensions




Photometric diagrams



CCT/CRI/Flux

CCT	CRI98	Flux
2700K	540 lm	
3000K	600 lm	
4000K	620 lm	

Code construction



Optionals



Note: the filter and the screen must be ordered together with the lighting fixture

AL7022
24VDC/500mA constant current converter

Drivers

500 mA	on/off	dimmable
AL1074 (1.2)	30mm IP20	AL4010 (1.4)
AL1077 (1.2)	40mm IP20	72mm IP20 PUSH 1..10V
AL1084 (1.3)	55mm IP20 S.P.	AL4151 (1.4)
AL9051 (1.3)	60mm IP67	72mm IP20 DALI
		AL4153 (1.4)
		60mm IP20 IGBT-TRIAC