

FLEXALIGHTING

LEAF 10 UGR

Recessed optic downlights

design Roberto Mantovani



A small and shallow recessed optic downlight characterized by a minimal design and high optical performance. Equipped with CRI85 or CRI93 LEDs, it lends itself to applications ranging from accent to general illumination and it can be fitted with an anti-glare filter for maximum visual comfort.

Incasso ad ottica arretrata caratterizzato da un design minimale e da alte prestazioni luminose. Offre la possibilità di combinare temperature colore ed aperture di fascio, con CRI85 o CRI93 ed è equipaggiabile con l'accessorio filtro antiabbagliamento, per assicurare il miglior comfort visivo dell'installazione.

Encastrable à plafond avec optique en retraite caractérisé par un design minimal et des performances optiques élevées. Équipé de LEDs avec CRI85 ou CRI93, il se prête à des applications allant de l'accentuation à l'éclairage général et il peut être équipé d'un filtre anti-éblouissement pour un confort visuel maximal.

Ein Einbaustrahler mit rückwärtiger Optik mit minimalistischem Design und hoher optischer Leistung. Ausgestattet mit CRI85- oder CRI93-LEDs eignet er sich für Anwendungen von Akzent- bis Allgemeinbeleuchtung und kann für maximalen Sehkomfort mit einem Blendfilter ausgestattet werden.

IP44 made in Italy



Supply current
500mA (V_i 18V)


Power
10W

Series wiring


CRI
85-93

2-Step MacAdam

Dimensions




Photometric diagrams



CCT/CRI/Flux

	CRI85	CRI93
2700K	890lm	840lm
3000K	1000lm	930lm
4000K	1040lm	960lm

Code construction



Accessories

LLFU101
Low luminance louver

SLFU101
Milky screen

Note: the filter and the screen must be ordered together with the lighting fixture

AL7022
24VDC/500mA constant current converter

Drivers

