

FLEXALIGHTING

LEAF 6

Flush optic downlight

design Roberto Mantovani



A range of recessed fixtures that combines an extremely refined and minimal design with a high visual comfort: the extremely thin edge and recessed optics make for an innovative and effective element. Equipped with Fidelity LED it places emphasis on CRI98 and R9 93. Available in three finishes, three colour temperatures and two extremely clean and performing optics.

Un gamma di incassi che associa un design estremamente curato e minimale ad un elevato confort visivo: il bordo estremamente ridotto e l'ottica arretrata ne fanno un elemento innovativo ed efficace. Equipaggiato con LED Fidelity si connota per un CRI98 e R9 93. Disponibile in tre finiture, tre temperature colore e due ottiche estremamente pulite e performanti.

Une gamme d'encastrables qui associe un design extrêmement soigné et minimaliste à un confort visuel élevé : le bord extrêmement réduit et l'optique en retrait en font un élément innovant et efficace. Équipé avec LED Fidelity il se caractérise par un CRI98 et R9 93. Disponible dans trois finitions, trois températures couleur et deux optiques extrêmement propres et performantes.



IP44 made in Italy

Una gama de empotrables que combina un diseño extremadamente preciso y minimalista con un alto confort visual: el borde extremadamente reducido y la óptica hacia atrás la convierten en un elemento innovador y eficaz. Equipado con LED Fidelity, se caracteriza por un CRI98 y R9 93. Disponible en tres acabados, tres temperaturas de color y dos ópticas extremadamente sutiles y de alto rendimiento.


Supply current
500mA (V, 9V)

Power
6W


Series wiring
CRI
98

2-Step MacAdam

Dimensions




Photometric diagrams



CCT/CRI/Flux

2700K	540 lm
3000K	600 lm
4000K	620 lm

Code construction



Accessories

LLF601
Low luminance louver



SLF601
Milky screen



Note: the filter and the screen must be ordered together with the lighting fixture

AL7022
24VDC/500mA constant current converter

Drivers

	on/off	dimmable
500 mA		
— AL1074 (1..2) 30mm IP20	— AL4010 (1..4) 72mm IP20 PUSH 0/1..10V	
— AL1077 (1..2) 40mm IP20	— AL4151 (1..4) 72mm IP20 DALI 2	
— AL1084 (1..3) 55mm IP20 S.P.	— AL4153 (1..4) 56mm IP20 PUSH IGBT-TRIAC	