


MINIJOS F2

Trimless projectors

design Roberto Mantovani



An adjustable projector for trimless recessed installation, characterized by a minimal design and high optical performance. It lends itself to accent lighting applications, giving the chance to combine various color temperatures and beam angles, with CRI98 and R9 93. Can be fitted with an anti-glare filter for maximum visual comfort.

Proiettore orientabile per installazione ad incasso trimless, connotato da un design minimale ed elevate prestazioni ottiche, si presta ad applicazioni che vanno dalla luce d'accento all'illuminazione generale. Offre la possibilità di combinare temperature colore ed aperture di fascio, con CRI98 ed R9 93. Equipaggiabile con l'accessorio filtro antiabbagliamento, per assicurare il miglior comfort visivo dell'installazione.

Un projecteur réglable pour une installation encastrée sans bordure, caractérisé par un design minimal et des performances optiques élevées. Il se prête à des applications d'éclairage d'accentuation, offrant la possibilité de combiner différentes températures de couleur et angles de faisceau, avec CRI98 et R9 93. Peut être équipé d'un filtre anti-éblouissement pour un confort visuel maximal.



IP20 made in Italy

Ein verstellbarer Projektor für den randlosen Einbau, der sich durch ein minimalistisches Design und eine hohe optische Leistung auszeichnet. Es eignet sich für Akzentbeleuchtungsanwendungen und bietet die Möglichkeit, verschiedene Farbtemperaturen und Abstrahlwinkel mit CRI98 und R9 93 zu kombinieren. Kann mit einem Blendschutzfilter für maximalen Sehkomfort ausgestattet werden.

Un proyector regulable para la instalación empotrada sin bordes, caracterizado por un diseño mínimo y un alto rendimiento óptico. Se presta a aplicaciones de iluminación de acento, dando la oportunidad de combinar varias temperaturas de color y ángulos de haz, con CRI98 y R9 93.

Supply current
500mA (V_f, 2,9V)


Power
2W

Series wiring


CRI
85

2-Step MacAdam

Dimensions



Photometric diagrams




CCT/CRI/Flux

2700K	128 lm
3000K	133 lm
4200K	154 lm

Code construction

MJSF2 X X X




Note: versions with extended arm length are available upon request

Accessories

ZQC001 ZQC001B
White Black

Plasterboard recessing frame



AL7022

24VDC/500mA constant current converter

Drivers

500 mA	on/off	dimmable
	AL1074 (1.7) 30mm IP20	AL4010 (1.12) 72mm IP20 PUSH 0/1.10V
	AL1077 (1.6) 40mm IP20	AL4151 (2.14) 72mm IP20 DALI 2
	AL1084 (1.11) 55mm IP20 S.P.	AL4153 (1.14) 56mm IP20 PUSH IGBT-TRIAC