

FLEXALIGHTING

MINIJOS R10

Semi-recessed projectors

design Roberto Mantovani



A projector for semi-recessed wall or ceiling installations, it is characterised by a minimal design and high optical performance. It lends itself to applications ranging from accent lighting to general illumination. Also available in a version with 10°-55° adjustable lens.

Proiettore per installazione a semi-incasso a parete o a soffitto connotato da un design minimale ed elevate prestazioni ottiche. Si presta ad applicazioni che vanno dalla luce d'accento all'illuminazione generale. Disponibile anche in versione ad ottica regolabile 10°-55°.

Projecteur pour installation semi-encastrée sur mur ou sur plafond, caractérisé par un design minimaliste et de hautes performances optiques. Il est indiqué pour les applications allant de l'éclairage d'accentuation à l'éclairage général. Disponible aussi en version à optique réglable 10°-55°.

Projektor für halbversenkte Wand- oder Deckenmontage mit minimalistischem Design und hoher optischer Leistung. Eignet sich für Anwendungen, die von der Akzentbeleuchtung bis zur Allgemeinbeleuchtung reichen. Auch in der Version mit 10°-55° verstellbarer Optik erhältlich.

Proyector para instalación semi-empotrado en pared o techo caracterizado por un diseño minimalista y un alto rendimiento óptico. Se presta a aplicaciones que van desde la iluminación de acento hasta la iluminación general. También disponible en versión de óptica ajustable de 10°-55°.



IP20 made in Italy

Supply current

500mA (V_i 18V)

Power

10W


Series wiring

CRI


85-93

2-Step MacAdam

Dimensions



Photometric diagrams




CCT/CRI/Flux

	CRI85	CRI93
2700K	890lm	840lm
3000K	1000lm	930lm
4000K	1040lm	960lm

Code construction

MJSR1 X X X X



Note: versions with extended arm length are available upon request

Accessories

LJ01 LJ01B

White Black

Low luminance louver



SJ01 SJ01B

White Black

Milky screen



Note: The filter and the screen are not available in adjustable optics version 10-55°

AL7022

24VDC/500mA constant current converter

Drivers

